



# MS-Bond 005 - 100 - 300 - 600

## PRODUCT TECHNICAL DATA SHEET



MS Bond

MS Bond

MS Bond

MS Bond

### USAGE:

MS-Bond 005, 100, 300 and 600 are each frame adhesives designed for bonding most types of substrates including mesh to frame. The low viscosity allows for rapid penetration between mesh and frame for rapid curing. Surfaces to be bonded must be clean and dry.

### ADVANTAGES:

1. Ideal for bonding fabric to wood, aluminum, plastics, and all types of metal.
2. Excellent strength for large format frame sizes. The overlap sheer tension is in excess of 3000lbs. in order to provide a longer lasting bond.
3. Rapid curing.

### APPLICATION:

#### Step 1:

Make sure all bonding surfaces are clean and dry.  
Stretch mesh on your stretching device.

#### Step 2:

Apply an even layer of instant adhesive using the applicator tip provided. Spread evenly and smoothly with a small squeegee. Though cure is initiated on contact, most bonds will achieve full cure in 24 hours. An application of MS-Bond Activator will cure and bond the surfaces together instantly.

### MS-BOND SELECTION GUIDE:

TYPE	MESH COUNTS
005	350 - 460
100	250 - 300
300	125 - 250
600	All Coarse Mesh

**\*\* ALWAYS READ THE MSDS \*\***

IMPORTANT: The technical data herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage, and handling of the product. No warrant, express or implied is intended including but not limited to, implied warranties of merchant ability and fitness for a particular purpose. Nothing contained herein shall be considered as a license to operate under, or recommendation to infringe any patents.



**MURAKAMI**

**MURAKAMI SCREEN USA, INC.** 745 Monterey Pass Rd. Monterey Park, CA 91754

TEL: 323.980.0662, FAX: 323.980.0659 [www.murakamiscreen.com](http://www.murakamiscreen.com)